



UTM data requirements

In order for UTM to support safe multiple UAS operations within and beyond visual line-of-sight, data related to weather, 3D structures, other aircraft, etc. must be made available. Describe the type of data needed to support safe operations, how that data is collected, maintained current, shared with operators, and whether standards for certain types of data are needed in terms of data quality (e.g. integrity, reliability, continuity and availability), security and resilience.

Drone Enable 2022 RFI



UTM Data Requirements

In order for UTM to support safe multiple UAS operations within and beyond visual line-of-sight, data related to weather, 3D structures, other aircraft, etc. must be made available. Describe the type of data needed to support safe operations, how that data is collected, maintained current, shared with operators, and whether standards for certain types of data are needed in terms of data quality (e.g. integrity, reliability, continuity and availability), security and resilience.

Drone Enable 2022 RFI



Non-repudiation

Protection against an individual who falsely denies having performed a certain action and provides the capability to determine whether an individual took a certain action, such as creating information, sending a message, approving information, or receiving a message.

- National Institute of Standards and Technology (NIST) SP 800-53 Rev. 5




Non-repudiation

Protection against an individual who falsely denies having performed a certain action and provides the capability to determine whether an individual took a certain action, such as creating information, sending a message, approving information, or receiving a message.

- National Institute of Standards and Technology (NIST) SP 800-53 Rev. 5



Why is non-repudiation important in UAS operations?



Increased Automation




Operator Collaboration



Building Trust



Operator-to-operator example



Systems exchanging data per standards and airspace requirements.







Something bad happens between ops managed by different entities

They were flying somewhere other than where they said they'd be.





They acknowledged our change of plans.

Did they do what they said they would do?

Are they denying seeing data they actually saw?



Not just operation service suppliers...



Operator receiving weather reports from a qualified provider



Operator ignores weather data or takes on excess risk, flying into bad conditions

You received a weather report and you didn't use it properly.





Operator claims a problem with weather service, insurance and weather provider disagree with operator



Message signing





Given appropriate infrastructure, it is possible to have each digital exchange signed, adding confidence that its content is unmodified and protecting against repudiation attacks against the system.





Proposed solution

Internet-Draft

Intended status: Standards Track Expires: 30 March 2023

A. Backman, Ed. J. Richer, Ed. Bespoke Engineering M. Sporny Digital Bazaar 26 September 2022

HTTP Message Signatures draft-ietf-httpbis-message-signatures-13

Abstract

This document describes a mechanism for creating, encoding, and verifying digital signatures or message authentication codes over components of an HTTP message. This mechanism supports use cases where the full HTTP message may not be known to the signer, and where the message may be transformed (e.g., by intermediaries) before reaching the verifier. This document also describes a means for requesting that a signature be applied to a subsequent HTTP message in an ongoing HTTP exchange.

Internet-Draft Obsoletes: 3230 (if approved) Intended status: Standards Track

Expires: 21 December 2022

R. Polli Team Digitale, Italian Government L. Pardue Cloudflare 19 June 2022

Digest Fields draft-ietf-httpbis-digest-headers-10

Abstract

This document defines HTTP fields that support integrity digests. The Content-Digest field can be used for the integrity of HTTP message content. The Repr-Digest field can be used for the integrity of HTTP representations. Want-Content-Digest and Want-Repr-Digest can be used to indicate a sender's interest and preferences for receiving the respective Integrity fields.

The Internet Engineering Task Force (IETF) has draft standards supporting non-repudiation of HTTP-based communications.

HTTP is the dominant approach to UAS Traffic Management (UTM) and xTM (extensible traffic management) system-to-system communications currently proposed, standardized, field-tested, and deployed around the world.

Careful consideration and implementation of these draft standards can close a gap that may otherwise derail faith and effectiveness of future UTM systems.

Currently being tested in the UTM Field Test in the USA. Regardless of those results, work would remain to fully vet and define requirements around message signing and non-repudiation.



Concluding thoughts

Repudiation of digital exchanges can undermine confidence and effectiveness of xTM systems.

Previously there have not been standardized approaches to non-repudiation for HTTP exchanges, despite the recognition that it is an important part of message security.

Advances in standardization of non-repudiation coincide with the maturation of xTM systems and should be incorporated as early as possible in the operationalization process.

We have proposed an approach leveraging standards and understanding the current state-of-the-art in xTM systems.

NASA/TM-20220016658



Non-Repudiation for Drone-Related Data

Joseph L. Rios Ames Research Center, Moffett Field, CA


Jaewoo Jung Ames Research Center, Moffett Field, CA

Marcus A. Johnson Ames Research Center, Moffett Field, CA

A detailed NASA Technical Memorandum on this topic is now available



Discussion and questions



Joseph Rios NASA Ames Research Center

joseph.l.rios@nasa.gov